

ROLL LABEL - COMMODITY

Issue date : 26/09/2016
Date last modification : 12/09/2019**4-RL1B-09195 - CAST GLOSS AP904 YG60 CERT. FSC®****Face Material**

Gloss white cast coated woodfree paper. FSC® certified.

Type	Cast coated paper	
Colour and Finish	White	
Weight	80 g/m ² ±10%	ISO-536
Thickness	78 µ ±10%	ISO 534

Adhesive

General purpose permanent acrylic adhesive

Reference	AP 904	
Type	Acrylic permanent	
Min. Appl. Temp.	+ 5 °C	
Service Temp.	-40°C/+100°C	
Shear	Medium	
Tack	13 N/25mm	FINAT FTM9
Final Adhesion	10 N/25mm	FINAT FTM2

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV and complies with FDA 175.105.

Liner

Type	Glassine paper	
Colour and Finish	Yellow	
Weight	58 g/m ² ±10%	PP-032 - ISO 536
Thickness	51 µ ±10%	ISO 534
Transparency	>45 %	DIN 53 147-64

Applications

Typical applications: for high gloss superior multicolour labels.

Printing Methods

Suitable for different printing systems: letterpress, flexo, offset and gravure.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

