

ROLL LABEL - COMMODITY

Issue date : 05/01/2005
Date last modification : 03/10/2019**4-RL1B-03119 COATED 120 AP904 YG60****Face Material**

Medium gloss white coated high grammage woodfree paper.

Type	Coated paper		
Colour and Finish	White		
Weight	115 g/m ² ±10%	ISO-536	
Thickness	96 µ ±10%	ISO 534-80	

Adhesive

Acrylic permanent adhesive. Good adhesion on a wide variety of materials including apolar substrates (like PE and PP).

Reference	AP904		
Type	Acrylic permanent		
Min. Appl. Temp.	+5°C		
Service Temp.	-40°C/+100°C		
Shear	Medium		
Tack	13 N/25mm	FINAT FTM9	
Final Adhesion	10 N/25mm	FINAT FTM2	

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV and complies with FDA 175.105.

Liner

Type	One side siliconised Glassine		
Colour and Finish	Yellow		
Weight	58 g/m ² ±10%	PP-032 - ISO 536	
Thickness	51 µ ±10%	ISO 534	
Transparency	>45 %	DIN 53 147-64	

Applications

Stiff labels for general and promotional use.

Printing Methods

Printable with UV letterpress, UV flexo, UV offset and gravure.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

