

**ROLL LABEL** - INDUSTRIAL

 Issue date : 05/01/2005  
 Date last modification : 25/01/2019

**4-RL2D-02491 RI-757/60 PP CAVITATED GLOSS WHITE TC RP1006 WG62**
**Face Material**

Gloss white top coated cavitated polypropylene.

Type	Top coated cavitated polypropylene	
Colour and Finish	Gloss white	
Weight	45 g/m <sup>2</sup> ±10%	ISO-536
Thickness	60 µ ±10%	ISO 534-80

**Adhesive**

Rubber based permanent adhesive featuring excellent substrate "wet-out" and very good ultimate adhesion for rough and apolar substrates (like PE and PP).

Reference	RP1006	
Type	Rubber permanent	
Min. Appl. Temp.	+5°C	
Service Temp.	-30°C/+60°C	
Shear	Medium	
Tack	15 N/25mm	FINAT FTM9
Final Adhesion	11 N/25mm	FINAT FTM2

This adhesive complies with FDA 175.105.

**Liner**

Type	One side siliconised Glassine	
Colour and Finish	White	
Weight	62 g/m <sup>2</sup> ±10%	PP-032 - ISO 536
Thickness	55 µ ±10%	ISO 534
Transparency	>45 %	DIN 53 147-64

**Applications**

For applications requiring a pearlescent look especially in the cosmetic industry, and for special applications, including applications on slightly rough surfaces. Not recommended for fan folder tags.

**Printing Methods**

Printing methods: UV letterpress, UV screenprinting, flexo UV, gravure and hot stamping. Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**

 24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.