

ROLL LABEL - COMMODITY

Issue date : 03/09/2015
Date last modification : 11/12/2018**4-RL1H-08848 THERMAL LASER CO2 RP1001 YG60****Face Material**

White top coated, thermal paper.

Type	Top coated thermal paper	
Colour and Finish	White	
Weight	84 g/m ² ±10%	ISO-536
Thickness	87 µ ±10%	ISO 534

Adhesive

Rubber based adhesive. High tack and adhesion, particularly on difficult apolar surfaces.

Reference	RP 1001	
Type	Rubber permanent	
Min. Appl. Temp.	0 °C	
Service Temp.	-20°C/+70°C	
Shear	Very high	
Tack	17 N/25mm	FINAT FTM9
Final Adhesion	10 N/25mm	FINAT FTM2

Liner

Type	One side siliconised Glassine	
Colour and Finish	Yellow	
Weight	58 g/m ² ±10%	PP-032 - ISO 536
Thickness	51 µ ±10%	ISO 534
Transparency	>45 %	DIN 53 147-64

Applications**Printing Methods**

Suitable for thermal printers and different printing systems.(Offset and Flexo).

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life12 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



Ritrama S.p.A.

Via Senatore Simonetta, 24
20867 Caponago (MB) ITALY
e-mail: info@ritrama.com
www.ritrama.com