

ROLL LABEL - Security Range

Issue date : 05/01/2005
Date last modification : 12/12/2016**4-RL3A-02351 RI-1901/50 PVC MATT WHITE AP905 WG90****Face Material**

Ultradestructible white cast vinyl.

Type	Cast vinyl
Colour and Finish	Matt white
Weight	100 g/m ² ±10% ISO-536
Thickness	50 µ ±10% ISO 534-80

Adhesive

Permanent acrylic adhesive, with excellent water, steam and temperature resistance. Very good UV resistance.

Reference	AP 905
Type	Acrylic permanent
Min. Appl. Temp.	+10°C
Service Temp.	-40°C/+120°C
Shear	Very High
Tack	15 N/25mm FINAT FTM9
Final Adhesion	12 N/25mm FINAT FTM2

Liner

Type	One side siliconised Glassine
Colour and Finish	White
Weight	90 g/m ² ±10% PP-032 - ISO 536
Thickness	77 µ ±10% ISO 534
Transparency	n.a. % DIN 53 147-64

Applications

Tamperproof labels that once applied has the characteristic of being ultra-destructible when tampered with, because the face material tears as pressure is applied.

Printing Methods

Printable in letterpress UV, screenprinting UV and thermal transfer.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life6 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

