

ROLL LABEL - COMMODITY

Issue date : 02/04/2015  
Date last modification : 18/10/2018**4-RL1B-08625 MATT SILVER AP904 YG60 FSC® CERTIFIED****Face Material**

Laminated of white paper and matt silver aluminium foil, top coated. FSC® certified.

Type	Laminated paper-aluminium	
Colour and Finish	Matt silver	
Weight	72 g/m <sup>2</sup> ±10%	ISO-536
Thickness	67 µ ±10%	ISO 534

**Adhesive**

General purpose, permanent. acrylic, water based adhesive.

Reference	AP 904
Type	Permanent, acrylic
Min. Appl. Temp.	+ 5 °C
Service Temp.	- 40°C / + 100°C
Shear	Medium
Tack	13 N/inch <sup>2</sup>
Final Adhesion	10 N/inch

**Liner**

Type	One side siliconised Glassine	
Colour and Finish	Yellow	
Weight	57 g/m <sup>2</sup> ±10%	PP-032 - ISO 536
Thickness	51 µ ±10%	ISO 534
Transparency	>50 %	DIN 53 147-64

**Applications**

Typical applications: for promotional and industrial labels, metallised effects.

**Printing Methods**

Suitable for different printing systems ( letterpress, flexo,offset and gravure ).

Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

