

INDUSTRIAL - INDUSTRIAL

Issue date : 31/01/2013
Date last modification : 17/09/2019**4-IL7A-04537 COATING 1223 D/PLUS WHITE ASP2D WG80DS****Face Material**

Matt white synthetic paper.

Type	Synthetic paper	
Colour and Finish	Matt white	
Weight	62 g/m ² ±10%	ISO-536
Thickness	80 μ ±10%	ISO 534-80

Adhesive

Acrylic permanent adhesive featuring very good ultimate adhesion suitable for very irregular surfaces.

Reference	ASP2D	
Type	Acrylic permanent	
Min. Appl. Temp.	+10°C	
Service Temp.	-40°C/+140°C	
Shear	Low	
Final Adhesion	7 N/25mm	FINAT FTM2

Liner

Type	2 side siliconised kraft	
Colour and Finish	White	
Weight	80 g/m ² ±10%	PP-032 - ISO 536
Thickness	90 μ ±10%	ISO 534

Applications

Label for the automotive and durable markets.

Printing MethodsPrinting methods: UV letterpress, UV screenprinting, gravure, hot stamping and thermal transfer.
Testing for suitability between media, printers and inks is always recommended prior to use.**Shelf life**24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.
All information is subject to change without prior notice.

