

ROLL LABEL - WINE LABELSIssue date : 16/07/2018
Date last modification : 22/02/2019**4-RL1C-10607 - GLACIER EXTRA WHITE WS AP903 WG74 FSC® CERTIFIED****Face Material**

Natural extra white water resistant paper featuring high opacity in wet conditions, FSC® certified.

Type	Natural felt-textured	
Colour and Finish	Extra white	
Weight	110 g/m ² ±10%	ISO-536
Thickness	138 µ ±10%	ISO 534-80

Adhesive

Acrylic permanent adhesive featuring good clarity. Excellent adhesion on a wide variety of materials, including apolar substrates (like PE and PP). This adhesive can be used on slightly rough surfaces.

Reference	AP903	
Type	Acrylic permanent	
Min. Appl. Temp.	-5°C	
Service Temp.	-40°C/+120°C	
Shear	Low	
Tack	8 N/25mm	FINAT FTM9
Final Adhesion	9 N/25mm	FINAT FTM2

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV .

Liner

Type	One side siliconised Glassine	
Colour and Finish	White	
Weight	72 g/m ² ±10%	PP-032 - ISO 536
Thickness	63 µ ±10%	ISO 534
Transparency	>40 %	DIN 53 147-64

Applications

High quality labels for beverage, wine and promotional uses.
Especially recommended for wine bottles requiring ice bucket immersion.
Not recommended for neck labels and small diameter bottles.
REELS MUST BE WOUND WITH THE FACE-SIDE OUT.

Printing Methods

Printable with lettepress UV, flexo UV, offset UV and gravure.
Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

18 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.
All information is subject to change without prior notice.

