

ROLL LABEL - Triplex Series

Issue date : 05/01/2005  
Date last modification : 09/12/2016**4-RT1B-02124 TRIPLEX COATED AP901 PET30/WG74****Face Material**

Triplex construction. Semi-gloss white coated woodfree paper.

Type	Coated paper
Colour and Finish	White
Weight	80 g/m <sup>2</sup> ±10% ISO-536
Thickness	65 µ ±10% ISO 534-80

**Adhesive**

Acrylic permanent adhesive featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP).

Reference	AP901
Type	Acrylic permanent
Min. Appl. Temp.	-5°C
Service Temp.	-40°C/+120°C
Shear	High
Tack	8 N/25mm FINAT FTM9
Final Adhesion	7 N/25mm FINAT FTM2

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV and complies with FDA 175.105.

**Liner**

Type	One side siliconised polyester
Colour and Finish	Clear
Weight	42 g/m <sup>2</sup> ±10% PP-032 - ISO 536
Thickness	30 µ ±10% ISO 534
Transparency	>95 % DIN 53 147-64

**Adhesive**

Acrylic permanent adhesive featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP).

Reference	AP901
Type	Acrylic permanent
Min. Appl. Temp.	-5°C
Service Temp.	-40°C/+120°C
Shear	High
Tack	8 N/25mm FINAT FTM9
Final Adhesion	7 N/25mm FINAT FTM2

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV and complies with FDA 175.105.

**Liner**

Type	One side siliconised Glassine
Colour and Finish	White
Weight	72 g/m <sup>2</sup> ±10% PP-032 - ISO 536
Thickness	63 µ ±10% ISO 534
Transparency	>40 % DIN 53 147-64

**Applications**

Flexible labels that allow to read the brand name under the material, once the frontal face is removed.

**Printing Methods**

Printable with letterpress UV, flexo UV, offset UV and gravure.

Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

