

Product code: 4-GL4A-08428

RASO WHITE SATIN ACETATE RP1005 PERMANENT WK135 NEUTRAL

Labels for fabrics, shoes, cards and mattress. Tamperproof labels.

The lay flat feature of the backing gives a great dimensional stability for Offset, litho and screen printing.

Applications

Fabrics, shoes, cards, mattress labels and promotional stickers.

Face Material

Gloss white acetate satin fabric with very good opacity.

Type	Acetate satin fabric	
Colour and Finish	White	
Weight	120 g/m ² ±10%	ISO-536
Thickness	140 µm ±10%	ISO 534-80

Adhesive

Rubber based very aggressive permanent adhesive featuring excellent tack on extremely difficult substrates, especially on apolar materials (like PE and PP).

Type	Rubber extra permanent	
Min. Appl. Temp.	+5 °C	
Service Temperature	-30°C/+50°C	
Shear	Medium	FINAT FTM8
Tack	23 N/25mm	FINAT FTM9
Final Adhesion	> 15 N/25mm	FINAT FTM2

Liner

Type	One side siliconised clay coated Kraft	
Colour and Finish	White	
Weight	135 g/m ² ±10%	ISO-536
Thickness	132 µm ±10%	ISO 534-80
Transparency	n.a. %	DIN 53 147-64

Printing Methods

Printable in solvent based screenprinting.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the storage conditions as defined by FINAT section 2.5:

- Ideal storage conditions are at a temperature of 20 -25 °C and 40 - 50 % HR.
- Store in a cool and dry place.
- Do not store close to a heat source or in direct sunlight.
- Keep the material in the original packaging until required for use.

Pay particular attention to the recommended shelf-life and ensure correct stock rotation

Disclaimer

All Ritrama's products are subject to manufacturing controls in order to guarantee the good quality of the products. The statements, technical information, data, values and recommendations regarding Ritrama's products are based on research and tests we believe to be reliable, but do not constitute a guarantee or warranty of whatsoever nature.

Considering the multiple uses of Ritrama's products, the user is recommended to test the products prior to their use, so to determine and ascertain the suitability and performance of the product for its intended application and purpose.

The methods of conversion and application of Ritrama's self-adhesive materials are multiple and it is therefore essential that the users are aware of the particular method to be used, prior to commencing the production.

Printing: Testing for compatibility between product, printers and inks is always highly recommended before printing the product.

Application Systems and Conditions: it is recommended that the performance of the product be always tested in the actual applications conditions as substrate state (rough, smooth, flat or irregular shapes, moderate curves, with or without rivets); applicator technology (hand application or fully automated lines); specific stress on Ritrama material once applied (high and/or low temperature, mechanical stress, exposure to challenging environment conditions), et cetera.

As Ritrama's products are used in conditions beyond its control, such as those listed above as example, Ritrama does not assume any liability for inappropriate use of the products.

Ritrama reserves the right to modify at any time and without the need of a prior notice, at its sole and exclusive discretion, the products, their features and technical specifications.

All Ritrama's products are sold subject to Ritrama's general terms and conditions of sale listed in the following Ritrama's web page: <http://www.ritrama.com/en/sale-conditions/>