

ROLL LABEL - COMMODITY

Issue date : 05/01/2005
Date last modification : 09/12/2016**4-RL2D-02528 RI-767/70 PP MATT WHITE TC MATT AP901 WG62****Face Material**

Matt white polypropylene top coated matt.

| | | |
|-------------------|--------------------------|------------|
| Type | Top coated polypropylene | |
| Colour and Finish | Matt white | |
| Weight | 52 g/m ² ±10% | ISO-536 |
| Thickness | 70 µ ±10% | ISO 534-80 |

Adhesive

Acrylic permanent adhesive featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP).

| | | |
|------------------|-------------------|------------|
| Reference | AP901 | |
| Type | Acrylic permanent | |
| Min. Appl. Temp. | -5°C | |
| Service Temp. | -40°C/+120°C | |
| Shear | High | |
| Tack | 8 N/25mm | FINAT FTM9 |
| Final Adhesion | 7 N/25mm | FINAT FTM2 |

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV and complies with FDA 175.105.

Liner

| | | |
|-------------------|-------------------------------|------------------|
| Type | One side siliconised Glassine | |
| Colour and Finish | White | |
| Weight | 62 g/m ² ±10% | PP-032 - ISO 536 |
| Thickness | 54 µ ±10% | ISO 534 |
| Transparency | >45 % | DIN 53 147-64 |

ApplicationsLabels where a matt finish is required.
Not recommended for fan folder tags.**Printing Methods**Printable with letterpress UV, screenprinting UV, gravure, hot stamping and thermal transfer.
Testing for suitability between media, printers and inks is always recommended prior to use.**Shelf life**24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



Ritrama S.p.A.

Via Senatore Simonetta, 24
20867 Caponago (MB) ITALY
e-mail: info@ritrama.com
www.ritrama.com