

ROLL LABEL - PHARMA

Issue date : 25/09/2009
Date last modification : 04/05/2018**4-RL2B-06369 RI-JET 675 ECO-UV PRINT GLOSS CLEAR AR807 REMOVABLE PET30****Face Material**

Gloss clear top coated polyester.

Type	Top coated polyester		
Colour and Finish	Gloss clear		
Weight	105 g/m ² ±10%	ISO-536	
Thickness	75 µ ±10%	ISO 534-80	

Adhesive

Removable adhesive with medium tack and good repositionability.

Reference	AR807 removable		
Type	Acrylic removable		
Min. Appl. Temp.	+10°C		
Service Temp.	-30°C/+100°C		
Shear	High		
Tack	6 N/25mm	FINAT FTM9	
Final Adhesion	4 N/25mm	FINAT FTM2	

Liner

Type	One side siliconised polyester		
Colour and Finish	Clear		
Weight	42 g/m ² ±10%	PP-032 - ISO 536	
Thickness	30 µ ±10%	ISO 534	
Transparency	>95 %	DIN 53 147-64	

Applications

For advertising and promotional applications (window graphics, outdoor and indoor posters, billboards and signs). Not recommended for fan folder tags.

Printing Methods

Ink jet UV technology, UV letterpress, UV screenprinting, gravure, hot stamping.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

